T-BAR HIGH VOLUME DIFFUSERS \$



HL Series - Architectural High Volume T-Bar Plaque Diffuser





PERFORMANCE DATA

	FPM		600			700			800			1000			1200	
	VP	-	0.022			0.031			0.04			0.062		0.075		
	CFM		325			380			435			540		650		
10"	SP	0.04				0.05			0.08			0.1		0.14		
	TP	0.062				0.081			0.12		0.162			0.215		
.542ft/sq.	NC	-		16			21		25			32				
	Throw	5	8	16	5	10	17	7	11	19	10	15	22	12	18	26

Features

- · Single plaque T-Bar diffuser
- · Designed for high volume air delivery
- · Delivers supply air in a 360° air pattern
- · Hinged and removable core for easy duct access
- 2" ADC compliant round collar with bead for ease of installation
- Collar sizes available in 6"-10", 12", 14", & 16"
- · Rust resistant pre-coat with durable powder finish
- · Soft White

Options

- Aluminum architectural T-Bar diffuser with fixed plaque face
- Adjustable baffle controllers to direct airflow horizontally or vertically
- · Fits 1x1 ceiling grids
- BD Field installable Bowtie Damper (available on even sizes 6"-14")
- Premium 3" round collar with bead (HL-3in)
- · Square Collar
- TVB Thermal Vapor Blanket
- NGD Narrow ceiling grid dimples for 9/16" T-Rails, changes 0.D. to 23 29/32"
- · Opposed Blade Radial Damper (Duct Mount Only)

HVL Series - 3 Cone High Volume T-Bar Diffuser



PERFORMANCE DATA

	FPM		600			700			800			1000		1200			
	VP		0.022	2		0.031	L		0.04			0.062		0.075			
	CFM	310				365			415			520		625			
10"	SP	0.07				0.095	5		0.12		0.16			0.215			
	TP	0.092				0.126			0.16		0.222			0.29			
.542ft/sq.	NC	25			30			34			40			43			
	Throw	6	10	18	8	12	19	9	13	21	11	16	24	13	20	27	

Features

- 3 cone steel diffuser with hinged core for easy duct access
- · Designed for high volume air delivery
- Delivers supply air in a 360° air pattern
- 2" ADC compliant round collar with bead for ease of installation
- Collar sizes available in 6"-10", 12", 14", and 16"
- Rust resistant pre-coat with durable powder finish
- Soft White

Options

- . Aluminum 3 cone T-Bar diffuser with fixed face (AA-HVL)
- Adjustable baffle controllers to direct airflow horizontally or vertically
- Fits 1x1 ceiling grids (collar size 6"-10")
- BD field installable Bowtie Damper (available on even sizes 6"-14")
- Premium 3" round collar with bead (HVL-3in)
- TVB Thermal Vapor Blanket
- Square Collar
- NGD Narrow ceiling grid dimples for 9/16" T-Rails, changes 0.D. to 23 29/32"
- Opposed Blade Radial Damper (Duct Mount Only)

T-BAR HIGH VOLUME DIFFUSERS SHOEMAKER



HVD Series – 4 Cone High Volume T-Bar Diffuser



PERFORMANCE DATA

	FPM	600				700			800			1000		1200			
	VP		0.022			0.031			0.04			0.062		0.075			
10"	CFM	310				365			415		520			625			
	SP	0.07				0.095	,		0.12		0.16			0.215			
	TP	0.092			0.126				0.16		0.222			0.29			
.542ft/sq.	NC	25		30			34			40			43				
	Throw	6	10	18	8	12	19	9	13	21	11	16	24	13	20	27	

Features

- · 4 cone steel diffuser with hinged core for easy duct access
- · Designed for high volume air delivery
- Delivers supply air in a 360° air pattern
- · 2" ADC compliant round collar with bead for ease of installation
- Collar sizes available in 6"-10", 12", 14", and 16"
- · Rust resistant pre-coat with durable powder finish
- · Soft White

Options

- · Aluminum 4 cone T-Bar diffuser with fixed face
- · Adjustable baffle controllers to direct airflow horizontally or vertically
- Fits 1x1 ceiling grids (collar size 6"-10")
- BD Field installable Bowtie Damper (available on even sizes 6"-14")
- Premium 3" round collar with bead (HVD-3in)
- · Square Collar
- TVB Thermal Vapor Blanket
- NGD Narrow ceiling grid dimples for 9/16" T-Rails, changes 0.D. to 23
- Opposed Blade Radial Damper (Duct Mount Only)

FTD Series – Fixed 4 Cone High Volume T-Bar Diffuser



PERFORMANCE DATA

	FPM	600				700			800			1000		1200			
	VP		0.022			0.031			0.04		1	0.062	!	0.075			
	CFM	310				365			415			520		625			
10"	SP	0.07				0.095	,		0.12		0.16			0.215			
	TP	0.092			0.126				0.16		0.222			0.29			
.542ft/sq.	NC	25		30			34			40			43				
	Throw	6	10	18	8	12	19	9	13	21	11	16	24	13	20	27	

Features

- · Fixed face 4 cone steel T-Bar diffuser
- · Designed for high volume air delivery
- Delivers supply air in a 360° air pattern
- · 2" ADC compliant round collar with bead for ease of installation
- Collar sizes available in even sizes 6"-14"
- · Rust resistant pre-coat with durable powder finish
- · Soft White

Options

- BD Field installable Bowtie Damper (available on even sizes 6"-14")
- Opposed Blade Radial Damper (Duct Mount Only)
- Preformed, contour molded fiberglass back with a foil barrier backing, compatible with 6-16" spin-in collar supplied by others (FTD-FBP)



Scan QR code to learn more about T-Bars at Shoemaker Manufacturing.