


# Fire Rated Submittal

U.L. Fire Resistance Classified Architectural T-Bar Plaque Diffuser

MODEL: HL-FR Series



### Standard Features:

- T-Bar assembly includes 2750 Series Ceiling Radiation Damper and TTB Series Thermal Blanket
- UL listed fire resistance T-Bar
- 3 hour rated fire resistance rating
- Building materials rated 3 hours or less
- Single plaque T-Bar diffuser
- Designed for high volume air delivery
- Delivers air in a 360° air pattern
- Hinged and removable core for easy duct access
- 2" ADC compliant round collar with bead for ease of installation
- Collar sizes available in 6"-10", 12", 14", & 16"
- Rust resistance pre-coat with durable powder finish
- Soft White



### Finishes:

#### STANDARD COLORS

- Soft White
- Driftwood Tan

#### DESIGNER COLORS

- Black
- Bronze
- Storm Gray
- Cement Gray
- Aluminum Paint
- Coffee Tan
- Warm White
- Glossy White



#### Maximum Product Height

DAMPER SIZE	HEIGHT (A)
6"	6 1/2"
7"	7"
8"	7 1/2"
9"	8"
10"	8 1/2"
12"	9 1/2"
14"	10 1/2"
16"	11 1/2"



### Additional Information:

### Submittal Notes

Project / Location:	
Engineer:	
Architect:	
Contractor:	