

3000P/3000OBD	Leakage Class			
DAMPER WIDTH	1in. wg	4in. wg	6in. wg	8in. wg
48"	I	II	II	II


Torque: 6.0 in.lb/sq.ft applied to close and seat the damper.



Shoemaker certifies that the 3000P and 3000OBD herein are licensed to bear the AMCA Seal. The ratings shown are based on the tests and procedures performed in accordance with AMCA publication 511 and comply with the requirements of the AMCA Certified Ratings Program. The AMCA International Certified Rating Seal applies to Air Performance and Air Leakage.

AMCA Certified Pressure Drop Data

AMCA 5.3



12"x12"	
VELOCITY (FPM)	PRESSURE DROP (IN.WG)
500	0.037
1000	0.170
1500	0.320
2000	0.700

24"x24"	
VELOCITY (FPM)	PRESSURE DROP (IN.WG)
500	.008
1000	0.040
1500	0.090
2000	0.170

36"x36"	
VELOCITY (FPM)	PRESSURE DROP (IN.WG)
500	0.004
1000	0.023
1500	0.041
2000	0.090

12"x48"	
VELOCITY (FPM)	PRESSURE DROP (IN.WG)
500	0.010
1000	0.042
1500	0.080
2000	0.170