

Performance Data



830-SS Series

Face Size	Neck Size	Neck Velocity, FPM	300	400	500	600	700	800	1000	1200	1400
		Vp, in. Wg	0.01	0.01	0.02	0.02	0.03	0.04	0.06	0.09	0.12
		Ps (-), in. Wg	0.03	0.06	0.09	0.13	0.17	0.23	0.36	0.51	0.7
12 x 12	6 Dia.	Flow Rate, CFM	59	78	98	118	137	157	196	235	275
		Room NC	-	-	-	14	18	21	27	32	36
	6 x 6 Neck	Flow Rate, CFM	75	100	125	150	175	200	250	300	350
		Room NC	-	-	12	17	21	24	30	35	39
	10 x 10 Neck	Flow Rate, CFM	208	278	347	417	486	556	694	833	972
		Room NC	15	23	29	33	37	41	47	51	55
24 x 24	6 Dia.	Flow Rate, CFM	59	78	98	118	137	157	196	235	275
		Room NC	-	-	-	13	17	20	26	31	34
	6 x 6 Neck	Flow Rate, CFM	75	100	125	150	175	200	250	300	350
		Room NC	-	-	-	14	18	21	27	32	35
	8 Dia.	Flow Rate, CFM	105	140	174	209	244	279	349	419	488
		Room NC	-	-	13	17	21	24	30	35	38
	8 x 8 Neck	Flow Rate, CFM	133	178	222	267	311	356	444	533	622
		Room NC	-	-	14	18	22	25	31	36	39
	10 Dia.	Flow Rate, CFM	164	218	273	327	382	436	545	654	763
		Room NC	-	-	16	20	24	27	33	38	41
	10 x 10 Neck	Flow Rate, CFM	208	278	347	417	486	556	694	833	972
		Room NC	15	11	17	21	25	28	34	39	42
	12 Dia.	Flow Rate, CFM	235	314	392	471	549	628	785	942	1099
		Room NC	-	12	17	22	26	29	34	39	43
	12 x 12 Neck	Flow Rate, CFM	300	400	500	600	700	800	1000	1200	1400
		Room NC	-	14	20	24	28	31	37	42	45
	14 Dia.	Flow Rate, CFM	320	427	534	641	748	855	1068	1282	1495
		Room NC	-	15	21	25	29	32	38	43	46
15 x 15 Neck	Flow Rate, CFM	469	625	781	938	1094	1250	1563	1875	2188	
	Room NC	-	16	22	26	30	33	39	44	47	
16 Dia.	Flow Rate, CFM	419	558	698	837	977	1116	1395	1674	1953	
	Room NC	11	18	24	28	32	35	41	46	49	
18 x 18 Neck	Flow Rate, CFM	675	900	1125	1350	1575	1800	2250	2700	3150	
	Room NC	11	18	24	28	32	36	41	46	49	
22 x 22 Neck	Flow Rate, CFM	1008	1344	1681	2017	2353	2689	3361	4033	4706	
	Room NC	13	20	26	30	34	37	43	47	51	
Other	10 x 22 (12 x 24 Face)	Flow Rate, CFM	458	611	764	917	1069	1222	1528	1833	2139
		Room NC	-	-	-	14	18	21	27	32	36
	14 x 14 (16 x 16 Face)	Flow Rate, CFM	408	544	681	817	953	1089	1361	1633	1906
		Room NC	-	-	12	17	21	24	30	35	39
	18 x 18 (20 x 20 Face)	Flow Rate, CFM	675	900	1125	1350	1575	1800	2250	2700	3150
		Room NC	-	11	17	22	26	29	35	40	44
	22 x 46 (24 x 48 Face)	Flow Rate, CFM	2108	2811	3514	4217	4919	5622	7028	8433	9839
		Room NC	12	20	25	30	34	38	43	48	52

Performance Notes:

- 1 Effective areas listed in chart are defined as the measurement of space between the blades actually being utilized by the air